



TECHNICAL INFORMATION & PLUS

FORMATI - SIZES



60x119.5
24"x48"
RETTIFICATO **66**



80x80
32"x32"
RETTIFICATO **65**



60x60
24"x24"
RETTIFICATO **54**
GRIP RETTIFICATO **55**




30x60
12"x24"
RETTIFICATO **51**



20x20
8"x8"
RETTIFICATO **75**

DECORI - DECORS



MOSAICO


30x30
12"x12" **115**



HEXAGON

30x34
12"x13" **34**


PEZZI SPECIALI - SPECIAL ITEMS



GRADINO
RETTIFICATO | GRIP

30x60
12"x24" **33**


30x60
12"x24" **34**



ELEMENTO A L
RETTIFICATO | GRIP

30x60x5
12"x24"x2" **49**


30x60x5
12"x24"x2" **50**



GRADONE COSTA RETTA
RETTIFICATO | GRIP

30x60x3,2
12"x24"x1,26" **115**


30x60x3,2
12"x24"x1,26" **118**



BATTISCOPA SMALTATO
RETTIFICATO

7x60
3"x24" **15**

7x80
3"x32" **24**



GRADONE ANGOLARE COSTA RETTA
RETTIFICATO | GRIP

30x30x3,2
12"x12"x1,26" **118**

30x30x3,2
12"x12"x1,26" **120**

CARATTERISTICHE TECNICHE - TECHNICAL FEATURES

	standards	characteristics or properties	declared values
	ISO 10545-3	assorbimento d'acqua water absorption	< 0.5%
	ISO 10545-4	resistenza alla flessione (R) breaking strength	35 N/mm ²
	ISO 10545-13	resistenza agli acidi resistance to acid	GLA
	ISO 10545-12	resistenza al gelo frost resistance	resiste frost proof
	ISO 10545-14	resistenza alle macchie stain resistance	4
	ISO 10545-2	planarità surface flatness	± 0.5%
		spessore thickness	9,5 mm
	DIN51097 DIN51130 ANSI A 137.1 DCOF BOT 3000 E	coefficiente d'attrito (scivolosità) dynamic coefficient of friction (slipperiness)	A+B R10 > 0.42
	DIN51097 DIN51130 ANSI A 137.1 DCOF BOT 3000 E	coefficiente d'attrito (scivolosità) dynamic coefficient of friction (slipperiness)	A+B+C R11 > 0.42
		variazioni cromatiche color shade	V2 variazione leggera V2 slight variation
		ortogonalità orthogonality	± 0.6%

IMBALLI - PACKING

cm inch		spessore thickness	pezzi/sc pcs/box	mq/sc sqm/box	kg/sc kgs/box	sc/pl box/pal	mq/pl sqm/pal	kq/pl kgs/pal
60x119.5 24"x48"	rettificato	9,5	2	1.44	33.84	27	38.88	914.00
80x80 32"x32"	rettificato	9,5	2	1.28	31.20	40	51.20	1248.00
60x60 24"x24"	rettificato grip	9,5	3	1.08	21.48	40	43.20	859.00
30x60 12"x24"	rettificato	9,5	6	1.08	21.60	48	51.84	1037.00
20x20 8"x8"	rettificato	9,5	16	0.64	13.51	72	46.08	972.72
30x30 12"x12"	mosaico		11	0.99	18.80	36	35.64	677.00
30x34 12"x13"	hexagon		6		12.78			
7x60 3"x24"	battiscopa smalt rett.		12		12.60			
9.5x80 4"x32"	battiscopa smalt. rett.		8		15.12			
30x60 12"x24"	gradino rettificato grip		8		31.20			
30x60 12"x24"	gradone costa retta rett. grip		4		17.20			
30x30 12"x12"	gradone ang. costa retta rett. grip		2		4.30			
30x60 12"x24"	elemento a L grip		4		17.20			

FUGHE - JOINT - JOINT - FUGE

per materiale rettificato prevedere una fuga di almeno 2 mm sul monoformato e necessariamente 3 mm sul multifformato
por rectified material, we recommend a 2 mm grout at least when using one size only and a 3 mm grout for multisizes laying solution
pour le matériel rectifié prévoir un minimum de 2mm de joint et 3mm pour la pose multifformat
fuer retifiziertes material-monoverlegung wollen sie bitte eine fuge von 2 mm vorsehen – fuer modulverlegung eine fuge von 3 mm